

Column 2 Vertical

Height mm	Length mm	Henrad Code	Heat emissions	
			Watts	Btu/hr
1800	348	313054	896	3055
	440	313055	1152	3928
2000	348	313056	994	3390
	440	313057	1278	4358
2500	348	313058	1260	4297
	440	313059	1620	5524

Btu/hr @ $\Delta t 50^{\circ}\text{C}$



For technical and installation information
visit our website www.henrad.co.uk/downloads

Due to production tolerances, the length of the product and therefore the tap centres could contain a variation of +/- 1.5% of the overall stated length.



Have you considered
Column Vertical Concept 2?

Technical information

Testing and Operating Pressures

Henrad Column 2 Vertical has been independently tested to ensure these radiators perform to a maximum working pressure of 10.0 bar.

Connections

Each radiator comes with $\frac{1}{2}$ " inlet connections as standard.

Paint Process

Two coat paint process, each Henrad radiator is subjected to a multi-stage cleaning and paint process.

The final powder coat is Traffic white (RAL 9016) which is stoved and cooled to give a perfect finish.
All radiators are illustrated in Traffic white unless stated.

Water Treatment

Installation of the system should be properly flushed and fitted in accordance with the British Code of Practice for the Treatment of Water in Domestic Hot Water Central Heating Systems.

Warranty

Henrad Column 2 Vertical comes with a 5 year manufacturer's warranty.

Henrad Column 2 Vertical

Wall Mounting Information

All dimensions in mm.

